### STRAIGHT FROM THE HEARTLAND



800-798-1968 SHIELDAG.COM



# **Quality Agricultural Equipment**

### **Manufacturers of:**

V-Blades • Sweeps • Chisels & Spikes • Disc Blades • Drill Discs & Hoe Drill Points Related Tillage & Planting Hardware • Fertilizer Knives • Shanks • Coulter Blades • Crop Savers Precision Planting Equipment • Conservation Ripper Points • Strip Till Points • Fertilizer Row Units

#### **Distributors of:**

Belted Grain & Fertilizer Conveyors • Salt & Material Handling Conveyors • Seed Handling Equipment Round Baler Belting • Milo Guards & Crop Savers

### **President**

Mike Bergmeier – Ext. 301 Email: mjbergmeier@shieldag.com

### **Vice President**

**Angie Bergmeier** – Ext. 311 Email: acbergmeier@shieldag.com

### **Sales Manager**

**Andy Klamm** – Ext. 305 Cell: 620-728-8630

Email: adklamm@shieldag.com

### **Office**

General Manager/Engineer

Logan Hurlbut – Ext. 315

Email: lhurlbut@shieldag.com

#### **Inside Sales**

**Paul Ehler** – Ext. 303 Cell: 620-728-8617

Email: prehler@shieldag.com

### Accounting/Parts Department

Iris Devena – Ext. 308

Email: iddevena@shieldag.com

### Shipping

Brenda Klug – Ext. 304

Email: shipping@shieldag.com

# **Warranty**

Acra-Plant warrants our products to be free of defects in materials and workmanship for a period of 180 days after the date of end user (consumer) purchase from the dealer. The warranty for whole goods equipment shall be exactly the warranty offered on these products by the original equipment manufacturer, and their individual warranties shall replace this warranty. This warranty does not apply to item(s), equipment or component parts that are found to have been subject to abuse or inadequate maintenance, that have been altered in any way or that have been used beyond their advertised capacity, rating or intended use. This warranty shall be for the repair or replacement of the defective item(s) at the sole discretion of Acra-Plant. Any warranty replacement or repairs shall be subject to prorated consumer usage deductions as outlined below. Any warranty on tillage items expires after 1/2" of edge wear has occurred. Chrome products are warranted for defects in material and workmanship only, and the pro-rating system and 1/2" edge wear rule does **not** apply to chrome products. Chrome products are not guaranteed for use in rocky or frozen ground. This warranty does not extend to labor incurred in removal or replacement of any item(s). Acra-Plant shall not be liable for incidental or consequential damages arising out of the use or inability to use the item(s) for any purpose whatsoever.

Execution of consumer rights for warranty repair or replacement:

- 1. Consumer must provide the dealer with evidence of date of purchase of the item(s) to be considered for warranty. This evidence shall be in the form of a copy of the invoice or bill of sale for the item(s) and this evidence shall accompany the item(s) alleged to be defective.
- 2. The dealer shall provide Acra-Plant with #1, above, and with a copy of the Acra-Plant invoice to the dealer for the same item(s).
- 3. The Acra-Plant Territory Manager or the dealer shall complete a Acra-Plant Returned Goods Authorization (RGA) for the item(s) alleged to be defective. It is the dealer's responsibility to return the item(s) to Acra-Plant at the dealer's expense; however, the Territory Manager may elect to return the items(s) to Acra-Plant via our truck. Extension of this courtesy does not constitute the final decision to authorize warranty replacement or repair for the item(s).
- 4. Upon receipt of the item(s) alleged to be defective and the RGA, the Acra-Plant engineering department will inspect the item(s). The engineering department will have sole discretion to authorize warranty replacement or repair.
- 5. Acra-Plant engineering department shall assign the pro-rated wear factors to all item(s) subject to a warranty claim. Since the range of item(s) varies widely, the assignment of pro-rated wear factor deductions shall be done in good faith, working with the Acra-Plant Territory Manager, the dealer and the consumer. In general, warranty will be prorated for wear up to 1/2" of edge wear on the item(s). Any warranty on tillage items expires after 1/2" of edge wear has occurred. The pro-rating system and 1/2" edge wear rule does **not** apply to chrome products.
- 6. Acra-Plant will at its sole discretion replace or repair the item(s) found to be defective, less the pro-rated wear factors. Acra-Plant will return the item(s) that have been repaired or replaced to the dealer including free return transportation via the mode of our choice.

#### **Notes on Implied Warranties and Limitations**

There is no implied warranty of merchantability or fitness for a particular purpose. Some states do not allow limitations on implied warranties of merchantability or fitness for a particular purpose, so this limitation may not apply in a given state. Some states do not allow the exclusion or limitation of incidental or consequential damages, so this limitation may not apply in a given state. This warranty gives dealers and consumers specific rights. There may be other rights that vary from state to state.

# **Shipments & Returns**

This "Shipments and Returns Policy" outlines the rights and obligations of Shield Agricultural Equipment (ShieldAg) dealers with regards to discrepancies in shipments and returns of unsold items to ShieldAg.

#### **Shipments**

ShieldAg must be informed of any shortages in shipments within ten (10) days of the arrival of that shipment or shipments at the dealer or end user (in the case of drop-shipments from ShieldAg to the end user). Shortages for truck shipments via LTL, UPS or other common carrier should be forwarded to the carrier for adjustment via freight claim. Shortages deemed by ShieldAg corporate office or our Territory Managers to be our responsibility will be corrected through a credit on the account of the dealer or through replacement of the item(s) that were missing from the shipment. It is the sole responsibility of the dealer to count the item(s) received on shipments and to make appropriate claims for shortages within ten (10) days of the receipt of the item(s).

Execution of dealer rights for shipments:

- Dealer shall provide ShieldAg with a copy of the ShieldAg packing slip (pick list) highlighting the item(s) that were alleged to be missing. A copy of the packing slip is to be faxed or mailed to ShieldAg within ten (10) days of the receipt of the shipment.
- 2. The ShieldAg Territory Manager may at our discretion be asked to visit the dealer and examine the shipment and shortage prior to extending credit or replacing the items.
- 3. ShieldAg will at its sole discretion replace the missing item(s) or credit the dealer account for the net dealer cost of the item(s) found to be missing. If replaced, ShieldAg will replace the missing item(s) to the dealer including free return transportation via the mode of our choice.

#### **Returns**

ShieldAg does not have any types of oral or written agreements, contracts or arrangements of any type, between ShieldAg and our dealers or distributors that provide for the rights and obligations of the parties with respect to the purchase or sale of equipment or repair parts, beyond the standard obligations created by purchase orders and acceptance of same, for ShieldAg parts. ShieldAg therefore does not fall under any state's "buy back" laws. ShieldAg will not allow returns for any items purchased as "special order" or non-standard as modified for a custom application. ShieldAg will accept the return of standard-stocked new item(s) originally purchased into dealer or distributor stock from ShieldAg for a period of two (2) years from the date of original purchase from ShieldAg. All items returned must be current to the stream of commerce and not deemed to be obsolete. Returned item(s) in new and merchantable condition shall be subject to a thirty percent (30%) restocking charge. Any item(s) requiring rework, repackaging or repainting will be accepted only with a revised (and increased) restock charge after inspection at ShieldAg.


Execution of dealer or distributor rights for returned goods:

- 1. Dealer or distributor shall provide ShieldAg with a copy of the original invoice for the item(s) to be returned and a written explanation of the reason for return.
- 2. The ShieldAg inside salesperson or territory manager will work with the dealer or distributor to complete a ShieldAg Returned Materials Authorization (RMA), also known in the industry as an RGA (Returned Goods Authorization) for the item(s) to be returned. Upon inspection of the original invoice and the written explanation for return, the ShieldAg Inside salesperson or territory manager will authorize return of the item(s) for inspection and subsequent credit. It is the dealer's responsibility to return the item(s) to ShieldAg at the dealer's expense. Receipt of items does not constitute the final decision to extend returned goods credit for the item(s).
- 3. Upon receipt of the item(s) and the completed RMA (RGA), ShieldAg will inspect the items for merchantability and general condition. Credit on account will only be applied after the items have been inspected and accepted. Credit against the dealer or distributor account receivable will be applied less the thirty percent (30%) restocking charge. There will be no cash refunds for returned items. The ShieldAg territory manager or inside salesperson will communicate (to the dealer or distributor) acceptance (or rejection) of the returned goods and the final credit amount.
- **4.** This Policy dated 12/01/2020 supersedes all previous written or oral Returned Goods polices.

Acra-Plant (	Quick Change Side-Mount Fertilizer Knives	Section 1
	Quick Change Fertilizer Knives for Chisel Plow ivator Applicators	Section 2
Acra-Plant H	Hoe Drill Shoes & Hoe Drill Points for OEM Replacement  Hoe Drill Shoes	
Chrome Car	Thide Ripper & Subsoiler Points  Conservation Ripper Points	4-4
Acra-Plant \	<i>I-</i> Slice Inserts	Section 5
Acra-Plant (	Cultivator Points & Sweeps	Section 6
Acra-Plant S	OEM Replacement Pin-on Cultivator Points	7-1 7-3 7-3
ShieldAg Pr	y Bars	Section 8
<b>Casting Cro</b>	ssover Index	Appendix



# Acra-Plant Quick Change Side-Mount Fertilizer Knives



\*For other fertilizer knives please call for your distributor

### **Features & Benefits**

- Acra-Plant replaceable point fertilizer knives outlast "throwaway" knives 3–5 times reducing downtime and saving money in the long run
- Chrome Carbide Points scour quickly to a high polish, slipping through the soil and pulling easier than "throwaway" knives you'll save more fertilizer with the unique self-sealing design
- Acra-Tuff Chrome Carbide alloy point continues to perform like new throughout its life with no degradation of performance after just a few hundred acres
- Acra knives are designed for minimum surface disturbance perfect for your No-Till cropping plan
- With a choice of three Acra-Tuff Chrome Carbide replacement points and many NH3 and liquid tube options, you can tailor your fertilizer rig to match your conditions and switch very easily if your crop rotation or nutrient plan changes

# **Acra-Plant Quick Change Side-Mount Fertilizer Knives**

<b>.</b>	Part#	Description	Weight
	AP-700010	Side mount shank with 3/8″ NH3 tube (.408″ OD, for 3/8″ NH3 hose)  Other tube options available, see options and replacement parts sections	4.60
	AP-700041	Standard fertilizer point with AP-510674  • 3/8″ x 1-3/8″ spring pin  • Self-sealing characteristics with minimum surface disturbance	4.29
	AP-700042-ST	Super Wing fertilizer point with AP-510674 • 5.0 3/8" x 1-3/8" spring pin • Aggressive hardpan fracturing point	5.0
	AP-700043	Super Wing fertilizer point with AP-510674  • 3/8' x 1-3/8' spring pin  • Aggressive hardpan fracturing point	4.0
	AP-700044	Closer fertilizer point with AP-510674  • 3/8" x 1-3/8" spring pin  • Aggressive hardpan fracturing point with added  • sealer wing for the toughest sealing conditions	4.69
	Starter Ass	emblies	
	Order ONE PAF	RT NUMBER to get started with Acra-Plant Knives:	

	Kit#	Description	Weight
	AP-700000	Assembly includes: AP-700010 shank with 3/8" NH3 tube (.408"OD, for 3/8" NH3 hose) AP-700041 standard point w/AP-510674 3/8" x 1-3/8" spring pin	8.89
	AP-700200	Assembly includes: AP-700010 shank with 3/8" NH3 tube (.408"OD, for 3/8" NH3 hose) AP-700043 Super Wing point w/AP-510674 3/8" x 1-3/8" spring pin	8.0
AP-700000	AP-700400	Assembly includes: AP-700010 shank with 3/8" NH3 tube (.408" OD, for 3/8" NH3 hose) AP-700044 sealer point with AP-510674 3/8" x 1-3/8" spring pin	8.0

AP-700000

# OPTIONS AVAILABLE to tailor your rig to your ground conditions and nutrient programs or BUILD YOUR OWN SYSTEM from the ground up:

Optional Acra knife shanks (WITHOUT ANY POINT)

Part#	Description	Weight
AP-700010	Shank with single 3/8" NH3 tube crimped and drilled	4.60
AP-700010V	Shank with 3/8" NH3 tube and 3/4" vapor tube	5.40
AP-700011	Bare shank without any tubes	4.00
AP-700011-XBR	Bare shank without any tubes	4.00
AP-702000	Shank with 3/8" NH3 and 3/8" liquid tubes (dual application) Front tube is crimped and drilled, rear tube is open end for liquid	0.50
AP-70200S	Shank with 3/8" NH3 and 3/8" STAINLESS liquid tubes (dual application) Front tube is crimped and drilled, rear tube is open end for liquid	5.10
AP-702010	Shank with 3/8" NH3 and 1/2 liquid tubes (dual application) Front tube is crimped and drilled, rear tube is open end for liquid	5.40
AP-702110	Shank with 3/8" NH3 and clip rings for 1/2" large plastic hose (dual application) Front tube is crimped and drilled and clip rings are welded on	4.80
AP-702510	Shank with single 1/2" NH3 tube (.569" OD), crimped and drilled	4.70
AP-702610	Shank with single 1/2" liquid tube (.569" OD), open end	4.70



NOTE: Specials and vapor tubes (Raven) available on request

### **Replacement Tubes & Parts**

Part#	Description	Weight
AP-700020	3/8" NH3 tube (.408" OD) crimped and drilled	0.50
AP-700021	3/8" Liquid tube (.408" OD) open end	0.50
AP-700022	1/2" Liquid tube (.569" OD) open end	0.60
AP-700023	3/8" NH3 tube (.408" OD) and clip rings for 1/2" large plastic tube	0.60
AP-700025	1/2" NH3 tube (.569" OD) crimped and drilled	0.60
AP-700041	Bare shank without any tubes	4.29
AP-700043	Bare shank without any tubes	4.00
AP-700044	Closer fertilizer point with AP510674 3/8" x 1-3/8" spring pin	4.69
K2TBDA3/4	3/4" Vapor tube (Raven)	0.75
AP-510674	3/8" x 1-3/8" spring pin	0.09






# **Additional Solid Chrome Carbide Coulter Injection**

Part#	Description	Weight
K-5SB5SST	Thin Boron knife for Ag Systems (and others)  Coulter Injection System comes with UHMW cushions to minimize impact damage  5/16" Thick Boron Steel Liquid Knife with Surta-Shield®	5.50
K-7S	Chrome knife for Ag Systems (and others)  No weld-on fertilizer steel tube, to reduce impact breakage  Customer just inserts 3/8" liquid hose into self-gripping deep hole cast into knife andties it off with band clamp or zip tie	4.35
K-8S	Chrome knife for Ag Systems (and others)  No weld-on fertilizer steel tube, to reduce impact breakage  Customer just inserts 3/8" liquid hose into self-gripping deep hole cast into knife andties it off with band clamp or zip tie	4.35





# Acra-Plant Quick Change Fertilizer Knives For Chisel Plow Applicators



- · Long-lasting Acra-Tuff Alloy replaceable points outwear "throwaway" chisel knives 3-5 times
- Acra-Tuff continues to perform like new throughout its life, no degradation of performance after just a few hundred acres
- Convert from fertilizer placement to standard chisel in just a few minutes by replacing the AP-708041 fertilizer point with the AP-705141 chisel plow point
- · AP-708041 fertilizer point protects your fertilizer tube from plugging, wear and freeze-up
- ube options available for nearly any NH3 or liquid application
- Set up to accept Acra-Plant Air Seeder assembly AP-718500 for maximum versatility with your chisel plow implement

Part#	Description	Weight
AP-708041	Acra-Tuff chrome alloy fertilizer point Includes AP-500657 1/2" x 1-1/4" spirol pin	2.79
AP-705042	Acra-Tuff chrome alloy chisel plow point Includes AP-500657 1/2" x 1-1/4" spirol pin	4.71
AP-705141	Acra-Tuff chrome alloy chisel plow point Includes AP-500657 1/2" x 1-1/4" spirol pin	4.80
AP-705011	4 Cast Steel Shanks	4.30
AP-708003	5 Adjusting wedge to change shank angle	0.50
AP-705029	Tube mounting bracket kit Includes: 1ea AP-705025 bracket 1ea AP-500536 1/4" U-bolt 2ea AP-500580 1/4 Lock Nut	0.50
AP-705021	3/8" Liquid tube (.408" OD), open end	0.32





# **Starter Assembly**Get started using your chisel plow for fertilizer application

Part#	Description	Weight
AP-705000	Complete shank with point, includes: • 1ea AP-705011 HT Steel shank • 1ea AP-708041 Fertilizer point with pin	7.50
	<ul> <li>1ea AP-708003 Adjusting wedge</li> </ul>	



### ORDER 1ea AP-705029 Tube Mounting Bracket Kit PER KNI

AP-705029	Tube mounting bracket kit 0.50 • Includes: 1ea AP-705025 bracket	6.50
	<ul> <li>1ea AP-500536 1/4" U-bolt</li> <li>2ea AP-500580 1/4" Lock Nut</li> </ul>	
	Zea Ai -300300 1/4 Lock Nut	



Left to right: AP-705027, AP-705021, AP-705023, AP-705024

# **Replacement Tubes**

Part#	Description	Weight
AP-705020	3/8" NH3 tube (.408" OD), crimped and drilled	0.32
AP-705021	3/8" Liquid tube (.408" OD), open end	0.32
AP-705022	1/2" Liquid tube (.569" OD), open end	0.34
AP-705023	3/8" NH3 and clip rings for 1/2" large plastic hose (dual application) Tube is crimped and drilled and clip rings vare welded on	0.46
AP-705024	1/2" NH3 tube (.569" OD) crimped and drilled	0.34
AP-705027	3/8" NH3 tube (.408" OD), crimped and drilled with 3 / 4 " Vapor tube welded on	0.79



AP-708041



AP-705042



AP-705141


# **Replacement Points**

Part#	Description	Weight
AP-708041	Acra-Tuff chrome alloy fertilizer point 2.19 Includes AP-500657 1/2" x 1-1/4" spirol pin	2.19
AP-705042	Acra-Tuff chrome alloy fertilizer point Includes AP-500657 1/2" x 1-1/4" spirol pin	4.71
AP-705141	Acra-Tuff chrome alloy chisel plow point 4.80 Includes AP-500657 1/2" x 1-1/4" spirol pin	4.80





# Acra Plant Field Cultivator Applicator System



### **Features & Benefits**

- Long-lasting Acra-Tuff Alloy replaceable points outwear "throwaway" points 3-5 times
- Acra-Tuff continues to perform like new throughout its life, no degradation of performance after just a few hundred acres
- AP-710080 fertilizer point protects your fertilizer tube from plugging, wear and freeze-up
- Tube options available for nearly any NH3 or liquid application
- May be used without tubes for standard cultivator work

Part #	Description	Weight
AP-710080 <b>①</b>	Acra-Tuff chrome alloy Z8 fertilizer point Includes AP-510693 5/16" x 1" spring pin	1.15
<u>AP-707611</u> <b>2</b>	Ductile iron field cultivator shank	3.75
AP-705029 <b>3</b>	Tube mounting bracket kit shin guard Includes: 1ea AP-705025 bracket 1ea AP-500536 1/4" U-bolt 2ea AP-500580 1/4" Lock Nut	0.50
AP-705023 <b>4</b>	3/8" NH3 and clip rings for 1/2" large plastic hose (dual application)  Tube is crimped and drilled and clip rings are welded on	0.46


NOTE: SEE REPLACEMENT TUBES & PARTS for all of the TUBE OPTIONS



2011 Acra-Plant Chrome Catalog 2-3

### **Acra-Plant Quick Change Fertilizer Knife for Field Cultivator Application**

#### Order these Part Numbers for First Time Use





### **ADD** the Fertilizer Tube of your choice:

Select the Replacement Fertilizer Tube(s) you need from the following:

Part #	Description	Weight
AP-705020	3/8" NH3 tube (.408" OD), crimped and drilled	0.32
AP-705021	3/8" Liquid tube (.408" OD), open end	0.32
AP-705022	1/2" Liquid tube (.569" OD), open end	0.34
AP-705023	3/8" NH3 and clip rings for 1/2" large plastic hose (dual application) Tube is crimped and drilled and clip rings are welded on	0.46
AP-705024	1/2" NH3 tube (.569" OD) crimped and drilled	0.34
AP-705027	3/8" NH3 tube (.408" OD), crimped and drilled with 3 / 4 " Vapor tube welded on	0.79

2ea AP-500580 1/4" Lock Nut



Left to right: AP-705027, AP-705021, AP-705023, AP-705024



# Acra-Plant Hoe Drill Shoes & Hoe Drill Points for OEM Replacement

# Retool Your Existing Hoe Drill with Acra-Plant to Improve Performance in Difficult Soil, Moisture & Residue Conditions

- Unique trash lifters allow for easier less-till planting
- Stainless steel bodies self scour to pull easier without plowing
- Acra-Tuff Chrome Carbide Points take the hardest ground

**Save on seed — Go deep to find moisture and protect young plants from high winds**without plowing the soil or raking your old stubble — plant in the heaviest of residues — **Use Acra V-Slice technology to put the seed where it belongs** this year. With Acra-Plant Hoe Drill Shoes, you can select from up to 5 different points to tailor your Hoe Drill for your ground and residue conditions.



AP-711070

John Deere LZ, 9300 775-785 Air Hoe Seeders



AP-719480

John Deere 9400 1800-Series Air Hoe Seeders



AP-714070

Crustbuster Hoe Drills with Trash Shank



AP-715070

CaselH 150 w/Cast Boot



AP-715570

CaselH 150 with Fab Boot



Acra-Plant Shoe with DSZ Point Assembly

Model #	Part #	Weight
John Deere LZ, 9300, 775–785 air hoe drills	AP-711070	4.08
(comes with AP-710070 (DSZ7) point installed)		
John Deere 9400, 1800-Series air hoe seeder	AP-719480	5.00
(comes with AP-710080 (DSZ8) point installed)		
Crustbuster hoe drills with trash shank	AP-714070	4.08
(comes with AP-710070 (DSZ7) point installed)		
CaseIH 150 hoe drills with cast boot	AP-715070	3.50
(comes with AP-710070 (DSZ7) point installed)		
CaseIH 150, 7000-7100-7200 hoe drills	AP-715570	3.33
with Fab Boot & 8500 air hoe drill		
(comes with AP-710070 (DSZ7) point installed)		

NOTE: Acra-Plant hoe drill shoes also available for Versatile/Noble drills. Consult factory for details. Installation hardware purchased separately.

2011 Acra-Plant Chrome Catalog 3-1




# John Deere LZ 9300, 775-785 Air Hoe Drills

Kit#	Description		Weight
AP-711070	Assembly Include	es	4.08
	AP-711052	Acra-Plant stainless steel drill shoe body weldment	3.05
	AP-710070	Acra-Tuff chrome carbide V-slice point (DSZ7) with pin	1.03

# Parts Required for First Time Installation on John Deere Drills

Part# Description		# Description		AP-711045 Installation Hardware	
AP-500044	Seed Baffle	1ea	3/8 x 2 1/2	Carriage Bolt	1ea
5/16 X 1	Hex Head Bolt	1ea	3/8	Top Lock Nut	1ea
5/16	Hex Jam Nut	1ea	5/16 x 2 1/2	Carriage Bolt	1ea
			5/16	Top Lock Nut	1ea

JD LZ/9300 Installation Sheet will be sent with each order for AP-711070



# **Optional Points & Hardware**

Part#	Description	Weight
AP-710060	(DSZ6) bolt-on V-bottom low disturbance point w/hardware	0.78
AP-710070	(DSZ7) bolt-on V-bottom low disturbance point w/ hardware	1.03
AP-729390	Z9 bolt-on flat bottom, drop-nose point without hardware	0.85
AP-729400	Bolt-on-heavy-duty shallow V, drop nose point without hardware	0.90
DNC-715V	Economy bolt-on shallow V, drop nose point without hardware	0.70
AP-510693	5/16" x 1" spring pin (comes with AP-710070)	
N1	1/4" square nut, required for bolt-on points	
Z1-1	1/4" x 1" machine screw slotted flat head, required for bolt-on points	
1-1	Box of 100ea 1/4" x 1" machine screw and 100ea 1/4" square nut	

With Acra-Plant Hoe Drill Shoes, you can select from up to five different points to tailor your Hoe Drill for your ground and residue conditions.

Hard Ground • Heavy Residue • Tough Planting Conditions

Dry Climate • Wet Planting Time

Tailor your Hoe Drill with Acra-Plant for Optimum Performance



## **John Deere 9400, 1800-Series Air Hoe Seeder**

AP-719480 Assembly with AP-710080 (DSZ8) Point

Kit#	Description		Weight
AP-719480	Assembly Include	es	5.0
	AP-719452	Acra-Plant stainless steel drill shoe body weldment	3.8
	AP-710080	Acra-Tuff chrome carbide V-slice point (DSZ8) with pin	1.20
AP-719670	Modified AP-7194	452 to acept AP-710060 or AP-710070	



# Parts Required for First Time Installation on John Deere Drills


Part# Description		t# Description		AP-711045 Installation Hardware	
AP-719421	Seed Baffle	1ea	3/8 x 2 1/2	Carriage Bolt	1ea
5/16 X 1	Hex Head Bolt	1ea	3/8	Top Lock Nut	1ea
5/16	Hex Jam Nut	1ea	5/16 x 2 1/2	Carriage Bolt	1ea
			5/16	Top Lock Nut	1ea

JD LZ/9300 Installation Sheet will be sent with each order for AP-711070

# **Replacement Point & Hardware**

Part#	Description	Weight
AP-710080	(DSZ8) pin-on heavy-duty V-slice point with pin	1.20
AP-510693	5/16" x 1" spring pin (comes with AP-710080)	

NOTE: The AP-719480 Acra-Plant Hoe Drill Shoe was designed EXCLUSIVELY for the John Deere 9400-series Hoe Drills and the 1800-Series Air Hoe Seeder. Optimum performance can only be guaranteed using the EXCLUSIVE AP-710080 (DSZ8) Heavy-Duty V-slice point.



# Optimize your John Deere Hoe Drill with ACRA-Plant Stainless Steel Hoe Drill Shoes






# **Crustbuster Hoe Drills Equipped with Trash Shanks**

Conversion For Crustbuster to Acra Plant Opener; AP-714070 Assembly with AP-710070


Kit#	Description		Weight
AP-711070	Assembly Includes	3	4.08
	AP-711052	Acra-Plant stainless steel drill shoe body weldment	3.05
	AP-710070	Acra-Tuff chrome carbide V-slice point (DSZ7) with pin	1.03



## **Hardware Installation Kit**

Kit#	Description	Quantity
AP-714071	3/8" x 2-1/2" carriage bolt	2
	3/8" top lock nut	2

Crustbuster Installation Sheet will be sent with each order for AP-71407



AP-714070

# **Optional Points & Hardware for Acra Plant Drill Shoe**

Kit#	Description	Weight
AP-710060	(DSZ6) bolt-on V-bottom low disturbance point w/hardware	0.78
AP-710070	(DSZ7) pin-on heavy-duty V-slice point with pin	1.03
AP-729390	Z9 bolt-on flat bottom, drop-nose point without hardware	0.85
AP-729400	Bolt-on-heavy-duty shallow V, drop nose point without hardware	0.90
DNC-715V	Economy bolt-on shallow V, drop nose point without hardware	0.70
AP-510693	5/16" x 1" spring pin (comes with AP-710070)	
N1	1/4" square nut, required for bolt-on points	
Z1-1	1/4" x 1" machine screw slotted flat head, required for bolt-on points	
1-1	Box of 100ea 1/4" x 1" machine screw and 100ea 1/4" square nut	

**Equip your Crustbuster Hoe Drill with ACRA-Plant Shoes** for HIGH PERFORMANCE Less-Till drilling





### **CaseIH 150 Hoe Drills with Cast Shank Boots**

### AP-715070 Assembly with AP-710070 (DSZ7) Point

Kit #	Description	• •	Weight
AP-715070	Assembly AP-71505	includes: 2 Acra-Plant stainless steel drill shoe body weldment	3.50 2.47
	AP-71007	O Acra-Tuff chrome carbide V-slice point (DSZ7) with pin	1.03
AP-715071	Hardware Quantity	Installation Kit Description	
	2	3/8" x 3/4" Carriage Bolt	
	2	3/8" Top Lock Nut	




# Parts Required for <u>First Time</u> installation on CaselH Drills

Part #	Description	Quantity	Weight
AP-715021	Seed baffle	1	0.20

CaselH 150 Cast Boot Installation Sheet will be sent with each order for AP-715070

### **Optional Points & Hardware**

Part #	Description	Weight
AP-710060	(DSZ6) bolt-on V-bottom low disturbance point with hardware	0.78
AP-710070	(DSZ7) pin-on heavy-duty V-slice point with pin	1.03
AP-729390	Z9 bolt-on flat bottom, drop-nose point without hardware	0.85
AP-729400	Bolt-on heavy-duty shallow V, drop nose point without hardware	0.90
DNC-715V	Economy bolt-on shallow V, drop nose point without hardware	0.70
AP-510693	5/16" x 1" spring pin (comes with AP-710070)	
N1	1/4" square nut, required for bolt-on points	
Z1-1	1/4" x 1" machine screw slotted flat head, required for bolt-on points	
1-1	Box of 100ea 1/4" x 1" machine screw & 100ea 1/4" square nut	



With Acra-Plant Hoe Drill Shoes, you can select from up to five different points to tailor your Case IH Hoe Drill for your ground and residue conditions

Hard Ground • Heavy Residue • Tough Planting Conditions
Dry Climate • Wet Planting Time

Acra-Plant will Tailor your Hoe Drill for Optimum Performance



# CaseIH 150 Hoe Drills with Fab Shanks & 7000-7100-7200 Hoe Drills with Fab Shank Boot & 8500 Air Hoe Drill



AP-715570

AP-715570 Assembly with AP-710070 (DSZ7) Point

Kit #	Description		Weight
AP-715570	Assembly includes:		3.33
	AP-715552 Acra-Plan body weld	t stainless steel drill shoe dment	2.30
	AP-710070 Acra-Tuff (DSZ7) wi	chrome carbide V-slice point th pin	1.03

# Optional Parts for <u>First Time</u> installation on CaselH Hoe Drills with Fab Boots


Consult Acra Plant Factory Engineering for side plates and seed tube options that may be required for FIRST TIME application:

Part #	Description	Quantity	
AP-715053	3/8" x 1" hex head cap screw	2	
Installation Hardware	3/8" top lock hex nut	2	
AP-715523 Optional Seed Tube	Short seed tube	1	

CaselH 150 Fab Boot Installation Sheet will be sent with each order for AP-715570

### **Optional Points & Hardware**







CaseIH Hoe Drills & Minimum-Till Drilling?

Do it this year with ACRA-Plant

Chrome Carbide Drill Points for Acra-Plant Min-Till Hoe Drill Shoes and Quality Chrome Carbide Drill Points to improve the performance of your standard hoe drill:

- · ACRA-Tuff Chrome Carbide Points take the hardest ground
- · Chrome Carbide will outlast OEM cast points 3-5 times
- · Many points available in V-bottom configuration, for improved seed-soil contact
- Widest variety of Chrome Carbide Points to tailor your hoe drill for your ground and residue conditions and for your ever-changing crop rotations

Part Numbers in bold are the Part Numbers you order from Acra-Plant/ShieldAg Part Numbers in parentheses () are common numbers that have been used by the industry to identify these parts



### See castings Cross Reference Index on pages i,ii, iii



### **Points Available for Acra-Plant Min-Till Hoe Drill Shoes**

Description

NOTE: These points are designed for drills that have been converted to Acra-Plant Shoes

Model #	Bolt-On V-Bottom	Pin-On V-Bottom	Bolt-On Flat Bottom	Bolt-On Shallow V	Economy Bolt-On Shallow V
John Deere	AP-710060	AP-710070	AP-729390	AP-729400	<b>DNC-715V</b>
LZ, 9300,775-785	(DSZ6, Z6)	(DSZ7, Z7)	(Z9)		(715V)
John Deere		AP-710080			
9400, 1800		(DSZ8, Z8)			
CaselH Fab Shank	<b>AP-710060</b> (DSZ6, Z6)	<b>AP-710070</b> (DSZ7, Z7)	<b>AP-729390</b> (Z9)	AP-729400	<b>DNC-715V</b> (715V)
CaselH Cast Shank	<b>AP-710060</b> (DSZ6, Z6)	<b>AP-710070</b> (DSZ7, Z7)	<b>AP-729390</b> (Z9)	AP-729400	<b>DNC-715V</b> (715V)
CrustBuster with Trash Shanks	<b>AP-710060</b> (DSZ6, Z6)	<b>AP-710070</b> (DSZ7, Z7)	<b>AP-729390</b> (Z9)	AP-729400	<b>DNC-715V</b> (715V)
Meloroe/Lilliston/ Kirshman/ Massey	<b>AP-710060</b> (DSZ6, Z6)	<b>AP-710070</b> (DSZ7, Z7)	<b>AP-729390</b> (Z9)	AP-729400	<b>DNC-715V</b> (715V)
Noble DK-5 2" shank	<b>AP-710060</b> (DSZ6, Z6)	<b>AP-710070</b> DK-5 Boot	AP-729390	AP-729400	
		to allow installati	ing tolerance, sides o on of point	f boot may have to	be ground slightly
Versatile 2000-220	0 Series	(DSZ8, Z8)			

(DSZ6, Z6) Bolt-on V-bottom point, includes hardware

(DSZ7, Z7) Pin-on V-bottom point with 5/16" x 1" spring pin

(DSZ8, Z8) Pin-on V-bottom point with 5/16" x 1" spring pin

(Z9, TF132) Bolt-on flat bottom point, without hardware

Bolt-on V-bottom point with "drop nose," without hardware

(715V) Bolt-on "economy" V-bottom point, without hardware

This point is a heavy-duty aggressive Acra-Plant V-bottom point

This point is a heavy-duty aggressive Acra-Plant V-bottom point

"drop point" designed for lighter soil applications

where the V-bottom is desired with a drop point

"drop point" designed for lighter soil applications

This point is a light-weight, less aggressive Acra-Plant V-bottom point without

designed for optimum seed-to-soil contact in the toughest planting conditions

designed for optimum seed-to-soil contact in the toughest planting conditions

This point is designed with a "drop nose" tip for any Z6 or Z7 application where the V-bottom is not desired due to ground or soil conditions

This point is designed with a "drop nose" tip for any Z6 or Z7 application

This point is a light-weight, less aggressive V-bottom point with a small







ľ	2	r	łv	U 9	ľ	ρ

Part #	Description
AP-510693	5/16" x 1" spring pin (comes with AP-710070)
N1	1/4" square nut, required for bolt-on points
Z1-1	1/4" x 1" machine screw slotted flat head, required for bolt-on points
1-1	Box of 100ea 1/4" x 1" machine screw & 100ea 1/4" square nut

3-8

Weight

0.78

1.03

1.20

0.85

0.90

0.70

# Points Available for John Deere OEM Hoe Drill Shoes

Model #	Standard Bolt-On Spear Point	Drop Nose Pin-On Flat Bottom	Drop Nose Bolt-On Flat Bottom	Spear Point Bolt-On V-Bottom
John Deere LZ John Deere 9300, 9400 with factory AN213462 boot &	<b>DNC-657D</b> (657)	<b>AP-729410</b> (Z10) (TF105) (657PO)	<b>DNC-657DEB</b> (657DEB)	<b>DNC-657V</b> (657V)
air hoe seeders		(657FO)		0

NOTE: John Deere OEM Boot Part Number AN213462 is now the only factory OEM boot available from John Deere for LZ, 9300 and 9400-series Hoe Drills. The above list of points are designed to yield the widest variety of Spear Points and V-bottom Points available today for all John Deere Hoe Drills and air hoe seeders using hoe drill boots.

### **Parts**

Part #	Description	Weight
DNC-657D	(657) John Deere bolt-on spear point <b>without hardware</b> The Spear Point is designed to replace the standard JD Spear Point and is a direct replacement for original LZ shoes	0.75
 AP-729410	(657PO, TF105, Z10) pin-on flat bottom point <b>without hardware</b> This point is designed with a "drop nose" tip for harder ground conditions and is a direct replacement for original LZ shoes	0.82
DNC-657DEB	(657DEB) "Drop-nose" bolt-on spear point without hardware This drop nose spear point is designed to replace the standard JD spear po in applications where customers require a shorter point while retaining the "drop point" design. Normally, all points must be replaced to use DNC-657D due to the shorter point design.	
 DNC-657V	(657V) Extended nose V-bottom bolt-on point without hardware This V-bottom Spear Point is designed to replace the standard JD Spear Point where a V-bottom design is required	0.86





AP-729410



DNC-657DEB



DNC-657V

### **Hardware**

Part #	Description
<u>N1</u>	1/4" square nut, required for bolt-on points
<u>Z</u> 1-1	1/4" x 1" machine screw slotted flat head, required for bolt-on points
1-1	Box of 100ea 1/4" x 1" machine screw and 100ea 1/4" square nut



# Points Available for CaselH/International OEM Hoe Drill Shoes

Model#	<b>Extreme Condition Bolt On Point</b>	Bolt-On V-Bottom
CaseIH/International	AP-720011X (720011)	AP-720011XV
	(809i)	

## **Parts**

Part#	Description	Weight
AP-720011X	(Z11X) Z11 extreme conditions bolt-on point, without hardware This point features a more radical nose drop and a taller V-crown to last longer in dry, hard conditions	0.90



AP-720011XV	Bolt-on V-bottom point, without hardware	1.04
	This point is a V-bottom version of the standeard 711	

# Hardware

Kit#	Description	
N1 1/4" square nut, required for bolt-on points		
Z1-3 1/4" X 1-1/2" machine screw slotted flat head, required for bolt-on points		



### Points Available for Crustbuster OEM Hoe Drill Shoes

Model #	Economy Bolt-On Point	Drop Nose Bolt-On V-Bottom
Crustbuster	<b>AP-729390</b> (Z9, TF132)	AP-729400

### **Parts**

Part #	Description	Weight	
AP-729390	(Z9, TF132) Bolt-on flat bottom point, without hardware This point is designed with a "drop nose" tip	0.85	
AP-729400	Bolt-on V-bottom point with "drop nose", <b>without hardware</b> This point is designed with a "drop nose" tip for any Z6 or Z7 application where the V-bottom is desired with a drop point	0.90	C



Part #	Description
N1	1/4" square nut, required for bolt-on point
<u>Z</u> 1-1	1/4" x 1" machine screw slotted flat head, required for bolt-on points
1-1	Box of 100ea 1/4" x 1" machine screw and 100ea 1/4" square nut

# Optional Points for Early Crustbuster Hoe Drills with $3/8^{''}$ shank and bolt-on point or pin-on options

Part #	Description	Weight
AP-710060	(DSZ6, Z6) Bolt-on V-bottom point with hardware	0.78
AP-710070	(DSZ7, Z7) Pin-on V-bottom point with 5/16" x 1" spring pin	1.03

2011 Acra-Plant Chrome Catalog 3-11

### **Points Available for Great Plains, My-D Han-D & Morris OEM Hoe Drill Shoes**

Model #	Standard Bolt-On Point	Drop-Nose Bolt-On V-Bottom	Bolt-On V-Bottom	Pin On V-Bottom
Great Plains,	AP-729390	AP-729400		
My-D Han-D	(Z9, TF132)		AP-710060	
Morris-MH310	AP-729390	AP-729400	AP-710060	AP-710080
Morris Edge on Shank				AP-7 10000

### **Parts**



Part #	Description	Weight
AP-729390	(Z9, TF132) Bolt-on flat bottom point, without hardware	0.85
	This point is designed with a "drop nose" tip	



AP-729400 Bolt-on V-bottom point with "drop nose", without hardware 0.90

### **Hardware**

Part #	Description
<u>N1</u>	1/4" square nut, required for bolt-on points
Z1-1	1/4" x 1" machine screw slotted flat head, required for bolt-on points
1-1	Box of 100ea 1/4" x 1" machine screw and 100ea 1/4" square nut

# **Optional Points for Early Great Plains Hoe Drills**



Part #	Description	Weight
AP-729400		1.03
DNC-715V	(715V) Bolt-on "economy" V-bottom point without hardware	0.70

NOTES: AP-710080 (DSZ8) only for drills with 1/2" shank option No roll pin for Great Plains drill point

WARNING NOTE: Check your application carefully before ordering. A trial fit may be needed to assure the correct fit with all points listed above

# Points Available for Versatile & Versatile/Noble Hoe Drills

Model #	Standard Bolt-On	Drop Nose	Drop Nose	Spear Point
	Spear Point	Pin-On Flat Bottom	Bolt-On Flat Bottom	Bolt-On V-Bottom
Versatile 2000-2200	<b>DNC-657D</b> (657)	<b>AP-729410</b> (Z10) (TF105) (657PO)	<b>DNC-657DEB</b> (657DEB)	<b>DNC-657V</b> (657V)







AP-729410





**DNC-657V** 

### **Parts**

Part #	Description	Weight
DNC-657D	(657) Bolt-on spear point, without hardware	0.75
AP-729410	(657PO, TF105, Z10) Pin-on flat bottom point, without hardware	0.82
DNC-657DEB	(657DEB) "Drop-nose point" bolt-on spear point, without hardware	0.78
DNC-657V	(657V) Extended nose V-bottom bolt-on point, without hardware	0.86

### **Hardware**

Part #	Description	
N1	1/4" square nut, required for bolt-on points	per 500
Z1-1	1/4" x 1" machine screw slotted flat head, required for bolt-on points	per 500
1-1	Box of 100ea 1/4" x 1" machine screw and 100ea 1/4" square nut	per 100

### Point for Versatile 2000-2200 Series with Acra-Plant 1/2" Shoe Foot

	2010ddio 2000 2200 001100 midi Mora i idilli, i/ 2	
Part #	Description	Weight
AP-710080	(DSZ8, Z8) Pin-on V-bottom point with pin	1.20

NOTE: Acra-Plant hoe drill shoes also available for Versatile/Noble drills. Consult factory for details.



AP-710080

### Point for very early 2000-series Versatile, 3/8" Foot

Part #	Description	Weight
AP-710060	(DSZ6, Z6) Bolt-on V-bottom point with hardware	0.78
AP-710070	(DSZ7, Z7) Pin-on V-bottom point with pin	1.03



AP-710060



AP-710070

WARNING NOTE: Check your application for Versatile & Versatile/Noble hoe drills carefully before ordering. A trial fit may be needed to assure the correct fit with all points listed above

# **Chrome Carbide Hoe Drill Points**



Part#	Description	Weight
AP-710060	(DSZ6, Z6) bolt-on V-Bottom, with hardware	0.78



AP-710070	(DSZ6, Z6) pin-on V-slice, with pin	1.03



AP-710080	(DSZ6, Z6) pin-on V-slice, point with pin	1.20



AP-720011X	(Z11X) bolt-on extreme conditions, without hardware	0.90



AP-720011XV 1.04 (Z11X) bolt-on extreme conditions, without hardware



AP-729390	(Z9, TF132) bolt-on drop-nose without hardware	0.85



AP-729400	Bolt-on V-bottom,	drop-nose without hardware	0.90



AP-729410 (Z10, 657PO, TF105) pin-on without hardware 0.82







# **Chrome Carbide Hoe Drill Points**

Part#	Description	Weight
DNC-657D	(657) bolt-on spear, without hardware	0.75
DNC-657DEB	(657DEB) drop nose bolt-on, without hardware	0.78
DNC-657V	(657V) V-bottom bolt-on Spear, without hardware	0.86
DNC-715V	(715V) economy bolt-on shallow V, without hardware	0.70
AP-720011XV	AP-720011XV bolt-on V-bottom point, without hardware	1.04





DNC-657DEB





DNC-715V



AP-720011XV

# Hardware

Part#	Description	Weight
AP-510693	5/16" X 1" Spring pin	_
N1	1/4" square nut, required for bolt-on points	
Z1-1	1/4" x 1" machine screw slotted flat head, required for bolt-on points	
Z1-3	1/4" x 1-1/2" Machine screw slotted flat head	
1-1	Box of 100ea 1/4" x 1" machine screw and 100ea 1/4" square nut	

# Chrome Carbide Ripper & Subsoiler Points

**Acra-Plant/ShieldAg** offers a full line of Chrome Carbide ripper and subsoiler points designed to handle tough, dry and hard ground conditions. We manufacture and stock points, shank guards, ripper caps and edge protectors for just about every make and model of subsoiler and disc ripper. Tough conditions that tear up and wear out stock/OEM points are **NO PROBLEM** for our exclusive Chrome Carbide designs.

**ShieldAg** combines proven Acra-Plant technology with up-to-date ShieldAg Engineering to provide long-lasting, self-sharpening Chrome Carbide deep tillage tools. All parts are made in the USA using the finest quality materials and a chrome carbide chemistry designed exclusively for our Midwest soil types. ShieldAg Chrome Carbide Ripper and Subsoiler Points are designed to last two to three times longer than the Original Equipment parts, and they self scour, wear sharp, and deflect soil flow away from the shank. Your customer saves on down-time, fuel and shank wear, adding dollars to their bottom line. Many different bolton, pin-on, and weld-on shank guards are designed just for most Rippers or Subsoilers.

ShieldAg Chrome Carbide ripper points are available for inter-row and shallow subsoiler applications. Our unique nose design takes the hardest ground and wears sharp. The crown reduces slabbing and diverts soil away from the shank to minimize wear. Chrome Carbide scours as it wears sharp to pull easier and reduce topsoil disturbance.

The farmer needing to deep rip with more lift and shattering between shanks will want one of our many types of "winged" ripper points. The scouring action of our Chrome Carbide will reduce fuel costs because the ripper will pull more easily.

Chrome Carbide Pin-on, clamp-on and weld-on shank guards are available for almost any shank. Chrome Carbide weld-on ripper caps are available from the factory on our alloy ripper point assemblies, or the cap can be sold separately for repairs and the do-it-yourself farmer.

Acra-Plant/ShieldAg Chrome Carbide tillage tools are perfect for tough ground conditions and conservation tillage plans.





2011 Acra-Plant Chrome Catalog 4-1



# Acra-Plant is Proud to Introduce the Future of Subsoiling Technology with our NEW LINE of Conservation Ripper Points.

Does your Conservation Tillage Yield improvement Program include Subsoiling or Disc/Ripping to relieve compaction zones and improve soil tilth?

### Acra-Plant has your answer with our NEW LINE of CRP Points designed to:

- Relieve soil compaction zones for YIELD IMPROVEMENT
- Improve SOIL TILTH to increase nutrient availability and root uptake
- Produce a subsoil profile that assures improved root penetration
- Assure moisture retention in the driest conditions
- Provide fracture and lift with little surface disruption or "slabbing"
- Allow flexibility in running depth
- Scour up, pull easy and flow soil around the shank to reduce wear
- Provide long wear life in the widest variety of soil conditions

The Acra-Plant & ShieldAg line of **CRP** ripper and subsoiler points are designed specifically for Conservation Tillage practices. **CRP** points are available with wings as shown here and without wings for inner row and spring fieldwork. Our unique design allows us to use solid 25% chrome carbide in all of the wear surfaces with mounting boots designed specifically for most popular makes and models of disc rippers and subsoilers. **Start your Conservation Tillage yield improvement prograit today** by asking for a CRPpoint for your disc ripper or subsoiler.





**Acra-Plant Subsoiler & Ripper Parts are made in the USA** 

# Points for Subsoilers & Rippers with 1" Thick Shank

1" Shank Designed for Krause 4650, Hamby, Johnson, Roll-A-Cone



•		
Part#	Description	Weight
TF-103	Spring cultivator point without hardware  • Shallow inter-row subsoiler point with V-crown design for reduced slabbing and surface sheeting  • Krause part number 33-161  • Interchanges with TF-122 (deep tillage point)  • Point is 2" wide x 5-1/2" long  • Casting # 103  NOTE: BC0001 Fits Both TF-103 & TF-122	2.68
TF-104	Shin guard for Krause 4650  • Krause part number 33-161A  • TF-104 is 1-1/4" wide x 13-3/4" long	6.50



TF-122 Deeper tillage and subsoiler point without hardware	3.00
<ul> <li>Wider version of TF-103 designed for subsoiling</li> </ul>	
<ul> <li>V-crown design for reduced slabbing</li> </ul>	
<ul> <li>Point is 2-1/2" wide x 5-1/2" long</li> </ul>	
Casting #122	
<ul> <li>Interchanges with TF-103 cultivator point</li> </ul>	

TF-122

### 1" Shank Designed for Krause 4650, Hamby, Johnson, Roll-A-Cone

Description



Part#

AP-800104

AG-8001-DF

	<u> </u>	
AP-800102	Orthman 2" wide point with AP-510730	3.62
	5/16"x1-3/4" pin	
	<ul> <li>Moderate depth (6"–8") with V-crown design</li> </ul>	
	<ul> <li>Point is 2-1/4" wide x 6" long</li> </ul>	
	<ul> <li>Casting # TF800102</li> </ul>	
	NOTE: This was ShieldAg part number AP-800101.	

Orthman 4" wide point with AP-510730

To align part numbers properly, we are changing the

NOTE: This was ShieldAg part number AP-800102. To align part numbers properly, we are changing



5/16"x1-3/4" pin
• Moderate depth (6"-8") with V-crown design
• 4" wide for increased shattering

part number to AP-800102

Point is 4" wide x 6" longCasting # TF800104

the part number to AP-800104



	without hardware • Moderate depth (6"-8") • Dorsal Fin further reduces slabbing and protects shank • Point is 2" wide x 8-1/2" long • Casting # TF800102	
AP-801100	Terra-Flow point for shanks with flat shin guard, without hardware  • Also fits AP-705011 chisel shank  • Point is 3-1/4" wide x8-1/2" long  • Casting # 801100	4.50

Orthman 2" wide dorsal fin suboiler point



AG-801100

Weight

4.81

5.00

### 1" Shank Designed for Big Ox & Lehman Rippers

Part#	Description	Weight
AP-800207	Big Ox ripper pin-on with AP-510730 5/16" x 1-3/4" pin (prior to 1986 "Big Ripper")  • Deep tillage point 6"–20" with V-crown design for reduced slabbing  • This point requires 5/16" hole in shank  • Excellent choice to repair worn shanks that will not accept the Big Ox slip-on points  • Will replace all 2D5-series Big Ox points  • Point is 2-1/4" wide x 7" long, casting #TF800207	3.33



Part#	Description	Weight
AP-800850	Big Ox Ripper pin-on with AP-510730 5/16" x 1-3/4" pin (1986 and later, including "Big Ripper")  • Deep tillage point 6"–20" with V-crown  • Wide point for aggressive deep tillage	3.75
N . Al		



Note: Also known as "Big Ox Point 2"

### Slip-on points for Big Ox & Lehman Rippers

Part#	Description	Weight
2D5	<ul> <li>Big Ox/Lehman slip-on point (prior to 1986</li> <li>"Big Ripper")</li> <li>Slip-on flat top ductile iron point without any cap</li> <li>Deep tillage point 6"-20" designed for very rocky soils or for customers building their own points</li> <li>Point is 1-3/4" wide x 6-1/2" long</li> </ul>	3.25



### 1" Shank Designed for Krause 4650, Hamby, Johnson, Roll-A-Cone

Part#	Description	Weight
2D5B	Big Ox/Lehman slip-on point (prior to 1986 "Big Ripper") • Slip-on flat top point with flat chrome carbide cap • Deep Tillage point 6"–20" • Point is 2" wide x 7" long	3.75
2D5BE	Big Ox/Lehman slip-on point (prior to 1986 "Big Ripper") • Slip-on extended point with extended chrome carbide cap • Deep Tillage point 6"–20" • Point is 2-1/4" wide x 7-1/2" long	4.00





### 1" Shank Designed for IHC # 10 & #11, Paulk, Big Ed, W&A

Part#	Description	Weight
AP-800900	V-crown design with AP-500659 3/8" x 2" pin • Deep tillage point 6"-20" • Point is 2-1/4" wide x 7" long, casting #800900	4.30



# Points for York Agri Products "Mulcher" Manufactured 1994 & Later

York Agri Products "Mulcher", Standard Point



Part#	Description	Weight
TF-8006-011	York Agri Products V-crown point without hardware  • This machine has a 1-1/4" thick shank with a 1" thick footpiece for mounting the ripper point  • Deep tillage point (6"-12")  • Excellent minimum surface disturbance point  • Point is 2-1/4" wide x 10" long  • Casting # TF8006-011	5.50

NOTE: For York Agri Products "Mulcher" machines manufactured 1993 and earlier, USE AP-800601, see page 4-7

### York Agri Products "Mulcher", Winged Point



Part#	Description	Weight
TF-8006-011W	York Agri Products winged point without hardware  • This machine has a 1-1/4" thick shank with a 1" thick footpiece for mounting the ripper point  • Winged version of TF-8006-011 for improved shattering  • Point is 6" wide x 10" long  • Casting # TF8006-011W	7.40

NOTE: For York Agri Products "Mulcher" machines manufactured 1993 and earlier, USE AP-800601W, see page 4-7





## Points for Subsoilers & Rippers with 1-1/4" Thick Shank

### Brent, Unverferth, IH #14, Lindsay Dammer-Diker without Dorsal Fin

Part#	Description	Weight
AP-800500	V-crown ripper point with AP-500646 7/16" x 2" pin  • Deep tillage point (6"–12")  • V-crown design for reduced slabbing  • Point is 2-3/8" wide x 10-1/2" long  • Casting # 800500	6.33



AP-800500

AP-800601

### JD 900, JD950V, P&M, P-K, Laney, Baker, Lehman Big Shank

Part#	Description	Weight
AP-800601	<ul> <li>V-crown ripper point with AP-500659 3/8" x 2" pin</li> <li>Acra-Plant's most popular Chrome Point</li> <li>Deep tillage point (6"-12")</li> <li>V-crown design for reduced slabbing</li> <li>An excellent choice for improved deep tillage for mos factory 1-1/4" shank deep rippers</li> <li>Point is 2-1/4" wide x 10" long</li> <li>Casting # 8006-01</li> </ul>	6.33



### JD 900, JD950V, P&M, P-K, Laney, Baker, Lehman Big Shank & Other 1-1/4" Shanks

Part#	Description	Weight
AP-800601W	V-crown ripper point with wings with AP-500659 3/8" x 2" pin Deep tillage point (6"–12") • V-crown design for reduced slabbing • All of the features of the AP-800601 with wings added for additional shattering capability—great for fracturing really dry, hard ground • Point is 6" wide x 10" long • Casting #8006-01W	6.40

Note: For York Agri Products "Mulcher" manufactured 1994 and later, see TF-8006-011W on Page 4-6



AP-800601W

### Brent, Unverferth, IH #14, Lindsay Dammer-Diker without Dorsal Fin

Part#	Description	Weight
AP-800800	V-crown ripper point with AP-500659 3/8" x 2" pin • Deep tillage point (6"-12") • V-crown design for reduced slabbing	5.50
	<ul> <li>Point is 2-1/4" wide x 10" long</li> </ul>	



Part#	Description	Weight
TF-81322	Deep tillage point 6"-20", without hardware  • Dorsal fin reduces slabbing and protects shank  • Point is 2" wide x 9" long	6.50





AP-800800



TF-81322

## Points for Subsoilers & Rippers with 1-1/4" Thick Shank

### Brent, Unverferth, IH #14, Lindsay Dammer-Diker without Dorsal Fin

Part#	Description	Weight
AP-800500	V-crown ripper point with AP-500646 7/16" x 2" pin  • Deep tillage point (6"–12")  • V-crown design for reduced slabbing  • Point is 2-3/8" wide x 10-1/2" long  • Casting # 800500	6.33



AP-800500

### JD 900, JD950V, P&M, P-K, Laney, Baker, Lehman Big Shank


Part#	Description	Weight
AP-800601	V-crown ripper point with AP-500659 3/8" x 2" pin  • Acra-Plant's most popular Chrome Point  • Deep tillage point (6"–12")  • V-crown design for reduced slabbing  • An excellent choice for improved deep tillage for mos factory 1-1/4" shank deep rippers  • Point is 2-1/4" wide x 10" long  • Casting # 8006-01	6.33



Note: For York Agri Products "Mulcher" manufactured 1994 and later, see TF-8006-011 on Page 4-6

#### JD 900, JD950V, P&M, P-K, Laney, Baker, Lehman Big Shank & Other 1-1/4" Shanks

8/8" x 2" pin Deep tillage point (6"–12") V-crown design for reduced slabbing All of the features of the AP-800601 with wings added for additional shattering capability—great for fracturin really dry, hard ground Point is 6" wide x 10" long	6.40





AP-800601W

### Brent, Unverferth, IH #14, Lindsay Dammer-Diker without Dorsal Fin

Part#	Description	Weight
AP-800800	V-crown ripper point with AP-500659 3/8" x 2" pin  • Deep tillage point (6"–12")  • V-crown design for reduced slabbing  • Point is 2-1/4" wide x 10" long	5.50



AP-800800

#### **Bush Hog Dorsal Fin Point**

Part#	Description	Weight
TF-81322	Deep tillage point 6"-20", without hardware  • Dorsal fin reduces slabbing and protects shank  • Point is 2" wide x 9" long	6.50



# Acra-Plant offers the ONLY full line of V-Crown Chrome Carbide Ripper Points for machines with 1-1/4" shanks

### **Acra-Plant Chrome Carbide V-Crown Subsoiler & Ripper Points**

# JD 900, JD950V, P&M, P-K, Laney, Baker, Bush Hog, Lehman Big Shank, Quinstar & other 1-1/4" shanks



Part#	Description	Weight
342-JD-238	<ul> <li>Pin-on flat top point, 2-3/8" wide cap without hardware</li> <li>An excellent choice for improved deep tillage for most factory 1-1/4" shank deep rippers</li> <li>An economical choice for deep ripping work</li> <li>Point is 2-1/2" wide x 12" long</li> <li>Casting # TF 238 12</li> </ul>	6.25
342-JD-278	<ul> <li>Pin-on flat top point, 2-7/8" wide cap without hardware</li> <li>An excellent choice for improved deep tillage for most factory 1-1/4" shank deep rippers</li> <li>An economical choice for deep ripping work</li> <li>Point is 3" wide x 12" long</li> <li>Casting # TF 278 12</li> </ul>	6.75

Note: These ripper points will interchange in applications using AP-800601 or AP-800601W solid chrome carbide points

### M&W & Sunflower Rippers & Disc Rippers with 1-1/4" Shank



Part#	Description	Weight
342-MW-238	York Agri Products winged point without hardware  • This machine has a 1-1/4" thick shank with a 1" thick footpiece for mounting the ripper point  • Winged version of TF-8006-011 for improved shattering  • Point is 6" wide x 10" long  • Casting # TF8006-011W	6.25
TB0034	Pin-on flat top point, 2" wide cap without hardware  • An excellent choice for improved inner row tillage  • An economical choice for deep ripping work  • Casting # TF1786 or B-178-6	
AP-800850	Pin-on flat top point, 1-15/16" wide cap without hardware  • An excellent choice for improved inner row tillage  • An economical choice for deep ripping work  • Casting # TF117 or F-200-4	
BC0001	<ul><li>B-C Ripper to Acraplant Adapter</li><li>An excellent choice for improved inner row tillage</li><li>An economical choice for deep ripping work</li></ul>	



Notes: This ripper point will interchange with CRP-4 if customer desires Conservation Ripper Point 42-MW-278 also available

# V-Crown Subsoiler & Ripper Points for Machines with 1-1/2" Thick Shank

### Caldwell, Graber & Laney Rippers



Part#	Description	weignt
AP-800700	V-crown ripper point with AP-500658 1/2 x 2-1/4" pin • Deep rillage point (6"-12")	8.50
	<ul> <li>V-crown design for reduced slabbing</li> </ul>	
	<ul> <li>Point is 2-1/2" wide x 11-1/2" long</li> </ul>	
	<ul> <li>Casting # TF800700</li> </ul>	
Landall 1600 Dril	lian 1 1/2 Chank Older Madel Tahhan Dinners with 1 1/2" sha	

AP-800700



Landoll 1600, Brillion 1-1/2 Shank, Older Model Tebbe	n Rippers with 1-1/2" shank
Tye & Bigham Brothers	

iye & Bignam Brothers		
TF-123	Point for Tye & Bigham Brothers, without hardware • ParaTill/ParaPlow offset shank rippers • Point is 2-1/2" wide x 8" long • Casting # TF123	6.10

### **Specialty Points for OEM Replacement**

The Acra-Plant Line of Blu-Jet Points have been redesigned to optimize the fit, lower draft requirements, improve the attack angle and provide more protection of the shank bottom

### **Blu-Jet Sub Tillers**

Part#	Description	Weight
AP-801300	<ul> <li>Inner-row point (also considered "spring point")</li> <li>Narrow point for deep tillage</li> <li>V-crown chrome carbide point scours up quickly and pulls easily</li> <li>Point is 2" wide x 14" long</li> <li>Casting # TF801300</li> </ul>	11.00



NOTE: Uses factory hardware, not supplied by Acra-Plant

Part#	Description	Weight
AP-801400	<ul> <li>Wide point (also considered "Fall point")</li> <li>Wider point for deeper tillage, more shattering action</li> <li>V-crown chrome carbide point scours up quickly and pulls easily</li> <li>Designed to run "nose-down" for optimum performance</li> <li>Point is 2-7/8" wide x 15-1/2" long</li> <li>Casting # TF801400</li> </ul>	16.00



NOTE: Uses factory hardware, not supplied by Acra-Plant

Part#	Description	Weight
AP-801600	Shin guard for Blu-Jet sub tiller Improved casting chemistry to resist breakage Guard is 1-1/4" wide x 22" long	14.50



NOTE: Uses factory hardware, not supplied by Acra-Plant

Part#	Description	Weight
AP-503300	Blu-Jet Spring (OEM) • Replaces casting # BJ3ASPRING/5033 or AP5033	7.0
AP-503200	Blu-Jet FALL (OEM) • Replaces casting # BJ3AFALL/5032 or AP5032	13.6





AP-503200

Part#



AP-800106	Orthman Strip-Till point	
711 000100	Diamond nose	
	<ul> <li>Tapered 2 ½" Wing</li> </ul>	
	<ul> <li>Use on 1" wide shanks</li> </ul>	
	<ul> <li>Improves upon Orthman part number 164-057</li> </ul>	

### **Acra-Plant VPS Rippers**

Optimize the performance of your VPS 2000 or VPS 3000 Ripper with Original Acra-Plant Chrome Carbide Points and Nickel Alloy Shin Guards

**Description** 

#### VPS 2000 – 1-Hole Shank Mount

Part#	Description	Weight
TF-820102	V-crown point with wings, VPS 2000 • Point is 3" wide x 9" long • Casting # TF820102	5.60
TF-820101	V-Crown Point, without wings, VPS 2000 • Same as TF-820102, without wings • Point Is 1-3/4" wide x 9" long • Casting # TF820101	4.80

NOTE: All VPS Ripper Points use factory hardware, not supplied by Acra-Plant.



TF-820102

# 1

### VPS 3000 - 2-Hole Shank Mount

Part#	Description	Weight
TF-820108	V-crown point with wings, VPS 3000 • Point is 4" wide x 10" long • Casting # TF820108	10.21

NOTE: All VPS Ripper Points use factory hardware, not supplied by Acra-Plant.



TF-820108

Part#	Description	Weight
TF-129	Nickel alloy shin guard for VPS 2000 and VPS 3000 • Replaces AP-820106 and TF-820106 • TF-129 is also designed for Quinstar, Baker and P-K rippers • TF-129 is 1-1/4" wide x 22-1/2" long	10.10

NOTE: We have improved the casting chemistry for 2004 to resist breakage in rocky or hard/frozen ground.

Uses factory hardware, not supplied by Acra-Plant.



AP-20406

### **Replacement Shanks available for VPS Rippers**

Part#	Description	Weight
AP-10420	1 1/4" Shank for VPS 2000	132.0
AP-20406	1-1/4" Shank for VPS 3000	88.0

NOTE: Improved using abrasion-resistant High Strength Steel.

\* Special Order Only

Weight 11.80

### Acra-Plant Nickel Alloy Shank Guards (Shin Guard) to replace cast OEM Shank Guards.


OEM Replacement Shank guards have been IMPROVED for 2010 using the latest in Nickel Alloy casting technology to improve resistance to fracture in rocky, frozen and hard ground with little degradation in wear life compared to Chrome Carbide.

Part#	Description	Weight
TF-104	Shin Guard for Krause 4650	6.50
	<ul> <li>Krause part number 33-161A</li> </ul>	
	<ul> <li>TF-104 is 1-1/4" wide x 13-3/4" long</li> </ul>	



NOTE: Uses factory hardware, not supplied by Acra-Plant

Part#	Description	Weight
AP-801600	Shin Guard for Blu-Jet Sub Tiller • Guard is 1-1/4" wide x 22" long	14.50



Part#	Description	Weight
TF-129	Shin Guard for VPS 2000 and VPS 3000 • Replaces AP-820106 and TF-820106 • TF-129 is also designed for Quinstar, Baker and P-Krippers • TF-129 is 1-1/4" wide x 22-1/2" long	14.50



AP-801600

NOTE: Uses factory hardware, not supplied by Acra-Plant

### **Weld-On Shank Guards & Wear Plates**

Acra-Plant Alloy Weld-on Shank Guards and Wear Plates protect or repair worn Subsoiler/
Ripper Shanks. Weld-on Shank Guards are segmented so that they may easily be broken into
sections to work on parabolic and odd-shaped shanks. These guards offer an economical way
to protect ripper shanks and repair worn shanks. Our unique Chrome Carbide chemistry scours
quickly and the segmented design breaks up dirt flow to minimize slabbing. All guards are cast
to be slightly wider than the shanks they protect to avoid scouring of the welds. Use 7018 welding
rod or Low Hydrogen Wire to weld these guards on.

### **Flat Top Weld-On Sectional Guards**

Part#	Description	Weight
SG-114-9	Flat top sectional guard, 1" wide x 9" long • Use on 3/4" wide shanks	1.00
SG-112-9	Flat top sectional guard, 1-1/2" wide x 9" long • Use on 1-1/4" wide shanks	1.10
SG-175-7	Flat top section guard, 1-3/4" wide x 7" long • Use on 1-1/2" wide shanks	1.00



### **Half-Round Weld-On Sectional Guards**

Part#	Description	Weight
SGR-114-14	Half-round sectional guard, 1-1/4" wide x 12" long • Use on 1" wide shanks	1.10
SGR-138-12	Half-round sectional guard, 1-3/8" wide x 12" long • Use on 1" or 1-1/4" wide shanks	1.80
SGR-112-14	Half-round sectional guard, 1-1/2" wide x 12" long • Use on 1-1/4" wide shanks	1.20



### Weld-On Shank Wear Plates, 3" x 6" x 5/16" thick

Part#	Description	Weight
TF-147L	Left-hand wear plate, weld-on, 15° parallelogram	1.60
SGR-138-12	Right-hand wear plate, weld-on, 15° parallelogram • Wear plates for just about any 15-degree straight shank • Beveled front edge to improve soil flow	1.60



### **Acra-Plant Alloy Weld-on Ripper Caps & Edge Guards**

Weld-on Chrome Carbide ripper caps offer an economical way to renew worn ripper points or build custom points to suit individual needs. Flat caps work great to extend the life of moldboard plow landsides and shares. Use 7018 welding rod or Low Hydrogen Wire to weld these caps on.

### Weld-On Flat Ripper Caps (wear caps), 5/16" Thick x 4" Long

Part#	Description	Weight
F-200-4	2" wide	0.70
F-212-4	2-1/2" wide	0.88





### **Weld-On Bump-Nose Ripper Caps**

These caps are similar to flat caps with the addition of a light bump at the nose to offer extended wear protection when used on rippers

Part#	Description	Weight
B-178-6	1-7/8" wide x 6" long	1.70
B-238-12	2-2/8" wide x 12" long	3.50
B-238-12	2-7/8" wide x 12" long	3.88



### **Weld-On Bump-Nose Ripper Caps with Bevel Front**

These caps are similar to Bump-nose caps with the addition of a ledge at the nose to fit over the ripper point base

Part#	Description	Weight
BE-238-7	2-3/8" wide x 7" long	2.25
BE-278-12	2-7/8" wide x 12" long	4.10



BE-278-12



Acra-Plant & ShieldAg offer the Widest Selection of High-Value Chrome Carbide Subsoiler & Ripper Points & Repair Parts in the Tillage Industry

### **Chrome Carbide General Application Edge Protectors**

от о		
Part#	Description	Weight
SI-12	<ul> <li>1"x 14" V-nose with 1/2" x 3/16" weld-on step</li> <li>SI-series V-nose edge protectors are perfect for potato digger blades</li> </ul>	1.11
SI-12HD	<ul> <li>1-3/4" x 12" V-nose with 1/2" x 3/8" weld-on step</li> <li>SI-series V-nose edge protectors are perfect for potato digger blades</li> <li>Casting #TF-106 SI-12HD</li> </ul>	2.17
SGT-12X1/2	<ul> <li>1/2" x 12" Triangular-shaped segmented guard</li> <li>3 segments are 4" long</li> <li>Perfect for welding to harrow tines or on pasture renovation equipment</li> </ul>	0.46
	SI-12 SI-12HD	SI-12  1"x 14" V-nose with 1/2" x 3/16" weld-on step SI-series V-nose edge protectors are perfect for potato digger blades  1-3/4" x 12" V-nose with 1/2" x 3/8" weld-on step SI-series V-nose edge protectors are perfect for potato digger blades Casting #TF-106 SI-12HD  SGT-12X1/2  1/2" x 12" Triangular-shaped segmented guard 3 segments are 4" long Perfect for welding to harrow tines or on pasture

### **Weld-On Segmented Guards**

Part#	Description	Weight
KTWS-01	9/16" x 6" Segmented Guard • 4 segments are 1-1/2" long	0.34
KTWS-02	3/4" x 6" Segmented Guard	0.49
KTWS-05	9/16" x 6" Fert. Knife Wear Shin	0.33
KTWS-06	3/4" x 1.96" Scraper Bit	0.17
KTWS-07		

KTWS-01

### **Acra-Plant V-Slice Inserts**

Made in the USA

Time-tested and improved V-slice inserts for just about any row crop planter or lister. Improve seed-to-soil contact in the toughest planting conditions with Acra-Plant V-slice technology. All Acra-Plant V-slice inserts either COME WITH hardware or use the Original Equipment hardware for ease of installation.

### Acra-Plant V-slice openers that replace **Original Equipment Seed Tube Guard/Inner Scrapers**

Part #	Description	Weight
AP-001685	<ul> <li>V-slice insert with pin/bolt White 6000 Series and later</li> <li>Designed for replacement of OEM seed tube guard/inner scraper</li> <li>Spring pin and bolt/nut provided with insert</li> </ul>	1.88
AP-001785	V-slice insert with pin/bolt John Deere & Kinze 2000  • Designed for replacement of OEM seed tube guard/inner scraper  • Spring pin and bolt/nut provided with insert	2.00
AP-001985XP	V-slice for John Deere 1700-series XP Row units  • Designed for replacement of OEM seed tube guard  • No hardware required, bayonet mount	2.24
AP-001885	Kinze 3000 series V-slice opener  • Designed for replacement of OEM seed tube guard/inner scraper  • Uses same socket head cap screws as OEM scraper	1.26

### Replacement V-slice Inserts for Acra-Plant Planter/Lister assemblies


Part #	Description	Weight
AP-410000	Acra-Plant tandem blade opener slicing blade with bolt  • Main replacement insert 10-C for Acra-Plant tandem blade opener	2.20
AP-410100	Acra-Plant tandem blade rear opener slicing stub withJ-bolt  • Short (rear) replacement insert for Acra-Plant tandem blade opener and V-9 Acra-Plant opener for CaselH 400-500 with offset discs	1.01
AP-954141	V-slice lister opener with J-bolt, 7-C • Replacement insert for Acra-Plant lister opener AP-959600	1.30

For complete descriptions of Acra-Plant No-Till planter/lister/drill enhancements, please see our Acra-Plant No-Till Catalog.









AP-954141





AP-1985V-SHOT

V-Slice proven technology, improving seed-soil contact

Uniform and early emergence, eliminate seed roll-and-bounce

Apply starter fertilizer WHERE IT BELONGS, below the seed



800-798-1968
WWW.SHIELDAG.COM



### **Chrome Carbide General Application Edge Protectors**

Part#	Description	Weight
AP-410601	IER3 slicing insert with pins  Replacement insert for Acra-Plant AP-009840 V-98 Opener  CaseLH 800-1200 planters  Casting #410601	1.28
AP-410602	V51 slicing insert with pins  • Replacement insert for Acra-Plant AP-034550 Opener  • White 5100 and 5700 planters  • Casting #410602	1.04





### Replacement V-slice Inserts for Acra-Plant Acra Drill Unit (ADU) and fertilizer attachments

Part#	Description	Weight
AP-A331100	ADU insert JDI3 with bolts/nuts for Acra Drill Unit • Replacement insert for Acra-Plant ADU • Casting # 331100	1.88
AP-API4L	Acra-Place insert, 19978 and later, left hand • Replacement insert for Acra-Plant fertilizer openers • Casting # 691241 ①	1.89
AP-API4R	Acra-Place insert, 1997 and later, right hand • Replacement insert for Acra-Plant fertilizer openers • Casting # 691240 (R)	1.89



AP-A331100

AP-API4L



For complete descriptions of Acra-Plant No-Till planter/lister/drill enhancements, please see our Acra-Plant No-Till Catalog.

All Acra-Plant V-slice attachments are MADE IN USA using the finest Acra-Tuff Chrome Carbide alloy for durability and long wear-life.

Our foundry uses state-of-the-art equipment and quality control procedures to assure TOP QUALITY and LONG LIFE.

### Cultivator Point: Sweens

## **Acra-Plant Cultivator Points & Sweeps**

Acra-Plant Acra-Tuff Alloy Points and Sweeps are made in USA and will wear 3–4 times longer than hardfaced high-carbon steel cultivator tools and up to 6 times longer than plain high-carbon tools! Acra-Plant points and sweeps will wear sharp and hold their shape throughout their long wear life. You'll reduce downtime, especially on really wide implements.

### All cultivator tools come with mounting hardware

### **Standard Mount Field Cultivator Tools**

Part #	Description	Weight
AP-871101	2-3/4" Field cultivator point, with hardware •2 Holes on 2" shank hole spacing •Casting # 871101	2.15

Part #	Description	Weight
AP-871201	2-3/4" Field cultivator point, with hardware	2.20
	<ul> <li>Hole and slot mounting accommodates 1-5/8" to 1-3/4" spacing</li> </ul>	g
	•Casting # 871201	



Part #	Description	Weight
AP-871107	7" Field cultivator sweep, with hardware and wedge  • Hole and slot for 1-5/8" to 2" shank hole spacing  • Casting # 871107	4.50



AP-871107

All of these points and sweeps come with mounting hardware





2011 Acra-Plant Chrome Catalog 6-1



### **Danish Tine Points & Sweeps ("S" Tines)**

Part#	Description	Weight
AP-860102	<ul> <li>1" Spike with neoprene shim and hardware</li> </ul>	0.80



AP-860202 • 2-1/2" Goosefoot with neoprene shim and hardware

1.10 · Single hole mounting

1.10

2.12

· Casting # 860202



AP-860402

• 4" Sweep with neoprene shim and hardware

· (4"OK sweep), single hole mounting

· Casting # 860402



AP-860402

AP-860702

• 7" Sweep with neoprene shim hardware

• (7" OK sweep), single hole mounting

· Casting #860702



AP-860702

### **Sweeps Designed for Kongskilde 3000-Series**

Part#	Description	Weight
AP-861202	<ul> <li>2-1/2" Sweep with hardware (no shim)</li> <li>2-hole mounting designed for Kongskilde 300-series (3500, 3800)</li> </ul>	1.70



AP-861202

NOTE: AP-861202 Kongskilde sweep comes with mounting hardware but does not include shim.



All of these points and sweeps come with a form-fitting neoprene shim and mounting hardware to assure perfect fit on your equipment



Adding Acra-Plant Chrome Carbide Components to your existing equipment will yield additional acres of wear life and reduced downtime.

Use Weld-On Points to repair worn parts or build your own custom tools.

### **OEM Replacement Pin-on Cultivator Points**

Part#	Description	Weight	
TF-130N	Orthman 164-043 point  • Improved for 2005 with Chisel Nose to enhance penetration and wear life	2.85	
	Casting # TF130 or TF130N		



## See SECTION 4 of this catalog for all of our chrome carbide ripper & subsoiler points



### **Chisel Plow**

Use 7018 welding rod or Low Hydrogen Wine to weld these parts. Consult factory for details.

#### **Weld On Chisel Point**



Part#	Description	Weight
TFN-1006	<ul> <li>Heavy-duty chisel point, 4-3/4" long x 3" wide</li> <li>Designed to weld on 3" twisted chisels, pocket underside to weld onto the end of chisel or fabricated spike</li> <li>Casting #TFN1006</li> </ul>	1.04

Cultivators, Sweeps, Chisel Plows or Listers Acra-Plant has solid chrome carbide points to help you improve performance and add wear life for the "Do-It-Yourself" farmer.



### **Rod Weeder Points**

Use Acra-Plant chrome carbide rod weeder points to improve the performance and wear life of your rod weeder.

Part#	Description	Weight
AP-890000	Calkins rod weeder point	2.11
	Casting #890000	
AP-890100	Flex King Rod Weeder Point	3.46
	<ul> <li>For Flex King, Miller/Morris and other large point rod weeders</li> </ul>	
	Casting #890100	





### **Chrome Carbide Points for Strip Till, Fertilizer & Chisel Plow Rigs**

All of these points are designed to weld on fabricated bar stock and are slightly wider than the bar stock they are designed to fit, to provide maximum protection from wear. Use 7018 welding rod or Low Hydrogen Wire to weld these parts. Consult factory for details.

Building your own fertilizer or strip till rig? We've got your point!



DF1PM-PO

2014 ACRA-PLANT CHROME CATALOG 7-3



INNOVATION IN AGRICULTURE.

## HD PRY-BARS

Our HEAVY-DUTY pry-bars are the hottest thing going for farm equipment dealerships & small fab shops. Take advantage of this hot selling pair of pry-bars today.

### SPB-1 DOUBLE HOOK BAR

· Dimensions: 1x1x45"

· Weight: 13 Lbs

### SHIELDAG

### SPB-2 POINT BAR W/HOOK

- 7° double taper
- Dimensions: 1x1x23"
- · Weight: 6.5 Lbs

### SHIELDAG

ShieldAg pry-bars are manufactured in the USA, from fine-grained, double-rolled 5160 chromium-manganese steel that's heated and tempered for 150,000 psi strength, durability and toughness that can't be matched.

- 5160 Chromium-Manganese
- Heat Treated & Tempered
- 150,000 psi Strength
- Made in the USA

STRAIGHT FROM THE HEARTLAND









Learn more details at:

SHIELDAG.COM





### **Acra-Plant/ShieldAg Part Number Conversions**

Catalog Number	Acra-Plant/ShieldAg Part Number	Description		Catalog Number	Acra-Plant/ShieldAg Part Number	Description	
11	AP-720011X	Drill Point		11CC	AP-720011X	Drill Point	
14	AP-729390	Drill Point		164-037	AP-800102	Ripper Point	
41	AP-700041	Fertilizer Point		164-039	AG-8001-DF	Ripper Point	
42	AP-700042	Fertilizer Point	OBSOLETE	164-041	AP-800104	Ripper Point	
44	AP-700044	Fertilizer Point		164-043	TF-130N	Cult Point	
66	AP-729400	Drill Point		5-919-606	AP-890000	Rod Weeder	
73	DNC-657D	Drill Point		657DEB	DNC-657DEB	Drill Point	
73	DNC-657DEB	Drill Point		657PO	AP-729410	Drill Point	
75	AP-729410	Drill Point		657V	DNC-657V	Drill Point	
087	TFN-1010	Lister Point	OBSOLETE	715V	DNC-715V	Drill Point	
98	AP-729390	Drill Point		716S	716S	Fertilizer Point	
99	AP-729400	Drill Point		73CC	DNC-657D	Drill Point	
103	TF-103	Ripper Point		73CC	DNC-657DEB	Drill Point	
122	TF-122	Ripper Point		75CC	AP-729410	Drill Point	
657	DNC-657D	Drill Point		78CC	TF-150	Renovator Point	OBSOLETE
8201	TF-820102	VPS Point		8006-01	AP-800601	Ripper Point	
8202	TF-820202	VPS Point		8006-01W	AP-800601W	Ripper Point	
52896	AP-801600	Shin Guard		8091	AP-720011X	Drill Point	
300136	TF-129	Shin Guard		809V	DNC-809V	Drill Point	OBSOLETE
331100	AP-331100	V-Slice Insert		98CC	AP-729390	Drill Point	
410601	AP-410601	V-Slice Insert		A11	AP-720011X	Drill Point	
410602	AP-410602	V-Slice Insert		A14A	AP-729390	Drill Point	
410901	AP-410901	V-Slice Insert	OBSOLETE	AG-7100-60	AP-710060	Drill Point	
500274	AP-708003	Wedge		AG-7100-70	AP-710070	Drill Point	
691240	AP-API4R	V-Slice Insert		AG-7120-00	AP-712000	Drill Point	
691241	AP-API4L	V-Slice Insert		AG-8001-DF	AG-8001-DF	Ripper Point	
700141	AP-700042	Fertilizer Point		AP-809-01	DNC-809V	Drill Point	OBSOLETE
705141	AP-705141	Chisel Point		AP12	AP-691042	V-Slice Insert	OBSOLETE
720011	AP-720011X	Drill Point		AP13L	AP-691041	V-Slice Insert	OBSOLETE
800500	AP-800500	Ripper Point		AP13R	AP-691040	V-Slice Insert	OBSOLETE
800900	AP-800900	Ripper Point		AG-809-01	DNC-809V	Drill Point	
801100	AP-801100	Ripper Point		AP12	AP-691042	V-Slice Insert	
801101	AP-801101	Ripper Point	OBSOLETE	AP13L	AP-691041	V-Slice Insert	
801200	AP-801200	Ripper Point	OBSOLETE	AP13R	AP-691040	V-Slice Insert	
860102	AP-860102	Danish Tine		AP14L	AP-API4L	V-Slice Insert	
860202	AP-860202	Goosefoot		AP14R	AP-API4R	V-Slice Insert	
860402	AP-860402	Sweep		APFC-1	AP-708041	Fertilizer Point	
860702	AP-860702	Sweep		ARP1	AP-800401	Ripper Point	
861202	AP-861202	Goosefoot		ASV1	AP-410901	V-Slice Insert	OBSOLETE
861402	AP-861402	Sweep	OBSOLETE	ATC1	AP-820105	Cap	OBSOLETE
871101	AP-871101	Cult Point		ATP1	TF-820101	VPS Point	
871107	AP-871107	Sweep		ATP2	TF-820102	VPS Point	
871109	AP-871109	Sweep	OBSOLETE	ATP4	TF-820108	VPS Point	
871201	AP-871201	Cult Point		ATS1	TF-129	Shin Guard	
890000	AP-890000	Rod Weeder		ATW1	AP-820103	Wing	OBSOLETE
890100	AP-890100	Rod Weeder		ATW2	AP-820104	Wing	OBSOLETE

## App

### **Acra-Plant/ShieldAg Part Number Conversions**

Catalog Number	Acra-Plant/ShieldAg Part Number	Description	
BJ3AFALL	AP-801400	Ripper Point	
<b>BJ3ASPRING</b>	AP-801300	Ripper Point	
BOP1	AP-800207	Ripper Point	
BOP2	AP-801000	Ripper Point	OBSOLETE
BRP1	AP-800601	Ripper Point	
CAP1	AP-708041	Fertilizer Point	
CCP-1	DNC-657D	Drill Point	
CCP-1	DNC-657DEB	Drill Point	
CCP4	AP-720011X	Drill Point	
CEL1	AP-954141	V-Slice Insert	
CEO1	AP-410000	V-Slice Insert	
CES1	AP-410100	V-Slice Insert	
CP20	AP-800102	Ripper Point	
CP5026	AP-801600	Shin Guard	
CP65	TF-65B	CaselH Rasp	
CP66	TF-66RB	CaseIH Rasp	OBSOLETE
CT-3	TFN-1005	Chisel Point	OBSOLETE
CUP1	AP-871101	Cult Point	
CUP2	AP-871201	Cult Point	
DNC4100	AP-410000	V-Slice Insert	
DNC4141	AP-954141	V-Slice Insert	
DNC559T	TF-123	Ripper Point	
DNC-757I	AP-720011X	Drill Point	
DNC8001	TF-122	Ripper Point	
DNC-809I	AP-720011X	Drill Point	
DNC-827P	AP-710070	Drill Point	
DNC-829	AP-710060	Drill Point	
DST1	AP-860102	Danish Tine	
DST2	AP-860202	Goosefoot	
DST4	AP-860402	Sweep	
DST7	AP-860702	Sweep	
DSZ10	AP-729410	Drill Point	
DSZ11	AP-720011X	Drill Point	
DSZ6	AP-710060	Drill Point	
DSZ7	AP-710070	Drill Point	
DSZ8	AP-710080	Drill Point	
DSZ9	AP-729390	Drill Point	
E1	AP-720011X	Drill Point	
	AP-729390	Drill Point	
	AP-729400	Drill Point	
FAD2	AP-699014	Chrome Wheel	OBSOLETE
FAD3	AP-699014 AP-699114	Chrome Wheel	OBSOLETE
FCP1	AP-705141	Chisel Point	0-00LL
FCS11	AP-871111	Sweep	OBSOLETE
FCS7	AP-871107	Sweep	
FCS9	AP-871109	Sweep	OBSOLETE
GRP1	AP-800700	Ripper Point	

Catalog Number	Acra-Plant/ShieldAg Part Number	Description	
HK-1P	TF-150	Renovator Point	OBSOLETE
IER3	AP-410601	V-Slice Insert	
IRP1	AP-800500	Ripper Point	
IRP2	AP-800900	Ripper Point	
JDI3	AP-331100	V-Slice Insert	
JDM2	AP-001785	V-Slice Insert	
JDSA	AP-957273	Seed Adapter	
JHZ1	AP-712000	Drill Point	OBSOLETE
JRP1	AP-800601	Ripper Point	
KMC1	AP-801500	Ripper Point	OBSOLETE
KRP1	TF-122	Ripper Point	
KST2	AP-861202	Goosefoot	
KST4	AP-861402	Sweep	OBSOLETE
KWRP1	AP-800601	Ripper Point	
LRP1	AP-801200	Ripper Point	OBSOLETE
MWRP1	AP-800800	Ripper Point	
NHP1	AP-700041	Fertilizer Point	
NHP4	AP-700044	Fertilizer Point	
NHP5	AP700042	Fertilizer Point	OBSOLETE
ORP1	AP-800102	Ripper Point	
ORP2	AP-800104	Ripper Point	
ORP3	AP-801100	Ripper Point	
ORP4	AP801101	Ripper Point	OBSOLETE
RWP1	AP-890000	Rod Weeder	
RWP2	AP-890100	Rod Weeder	
SAB1	AP-300039	ADU Spring Bar	
SI-12HD	SI-12HD	Edge Guard	
SR9175	TF-66RB	CaselH Rasp	OBSOLETE
SR9336	TF-65B	CaselH Rasp	
SSPL	AP-880001	Soil Saver	OBSOLETE
SSPR	AP-880000	Soil Saver	OBSOLETE
TF CC 13	TF-CC13	Knife Edge	OBSOLETE
TF CC 13 1	TF-CC13-1	Knife Edge	OBSOLETE
TF102	TF-102	Cut Point	OBSOLETE
TF105	AP-729410	Drill Point	
TF106	SI-12HD	Edge Guard	
TF111	AP-710060	Drill Point	
TF123	TF-123	Ripper Point	
TF130	TF-130N	Cult Point	
TF130N	TF-130N	Cult Point	
TF132	AP-729390	Drill Point	
TF148	TF-148	Golden Spike	OBSOLETE
TF150	TF-150	Renovator Point	OBSOLETE
TF238 12	342-JD-238	Ripper Point	
TF278 12	342-JD-278	Ripper Point	
TF66RB	TF-66RB	CaslH Rasp	OBSOLETE
TF700041	AP-700041	Fertilizer Point	
TF700044	AP-700044	Fertilizer Point	

### **Acra-Plant/ShieldAg Part Number Conversions**

	A DI 1/01::::		
Catalog Number	Acra-Plant/ShieldAg Part Number	Description	
TF800102	AP-800102	Ripper Point	
TF800104	AP-800104	Ripper Point	
TF800207	AP-800207	Ripper Point	
TF8006-011	TF-8006-011	Ripper Point	
TF8006-011W	TF-8006-011W	Ripper Point	
TF800700	AP-800700	Ripper Point	
TF801300	AP-801300	Ripper Point	
TF801400	AP-801400	Ripper Point	
TF82010 1	TF-820101	VPS Point	
TF820102	TF-820102	VPS Point	
TF820107	TF-820107	VPS Point	
TF820108	TF-820108	VPS Point	
TFN1005	TFN-1005	Chisel Point	OBSOLETE
TFN1006	TFN-1006	Chisel Point	
TFN1010	TFN-1010	Lister Point	OBSOLETE
TFRP1	AP-801400	Ripper Point	
TSRP1	AP-801300	Ripper Point	
WAW1	AP-034550	Wedge	
WHI1	AP-410602	V-Slice Insert	
Z10	AP-729410	Drill Point	
Z11	AP-720011X	Drill Point	
Z6	AP-710060	Drill Point	
<b>Z</b> 7	AP-710070	Drill Point	
Z8	AP-710080	Drill Point	

Casting Number	Acra-Plant/ShieldAg Part Number	Description
809V	AP-720011XV	Drill Point
DNC-809V	AP-720011XV	Drill Point
705042	AP-795042	Chisel Plow Fertilizer Point
AP-800105	AP-800106	Strip Till Point
BJ3AFall	AP-505200	Ripper Point
BJ3ASpring	AP-503300	Ripper Point
1685	AP-001685	V-Slice
1785	AP-001785	V-Slice
1785VS	AP-001785VS	V-Slice
1885	AP-001885	V-Slice
1985XP	AP-001985XP	V-Slice
1985XPVS	AP-001985XPVS	V-Slice
164-050	AP-800106	Strip Till Point
164-054	AP-800106	Strip Till Point
164-057	AP-800106	Strip Till Point


All Acra-Plant Chrome Carbide Products are MADE IN USA using the finest Acra-Tuff alloy for durability and long wear-life. Our foundry uses state-of-the-art equipment and quality control procedures to assure TOP QUALITY and LONG LIFE.







# STRAIGHT FROM THE HEARTLAND SHIELDAG.COM



### CALL THE DEALER NEAREST YOU

PHONE: (620) 662-7221 (800) 798-1968

FAX: (620) 662-7482

MAILING: PO BOX 687 • HUTCHINSON, KS 67504

SHIPPING: 950 SCOTT BLVD • SOUTH HUTCHINSON, KS 67505





